


ECLIPSE MODULAR SYSTEM SPECIFICATION SHEET

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____



DESIGN | ECLIPSE

ECLIPSE is a suspension light that can be a versatile and captivating addition to any space. Composed of rings that represent endless possibilities, allowing you to craft your own unique composition specific to your preferences. Embrace the freedom to choose the number, size, distance, and angle between the rings, giving birth to a lighting installation that reflects your project. Whether you prefer a compact, intimate cluster or a grand, expansive display, Eclipse adapts to your vision.



It also sets itself apart with its innovative chip-on-board LEDs, offering a distinctive look and feel that distinguishes the fixture, bringing a modern, cutting-edge allure.


SYSTEM OVERVIEW



PROJECT _____
 TYPE _____
 NOTES _____
 QUANTITY _____
 DATE _____

SYSTEM GUIDE

To make your product selection and complete system specification, proceed with the following:
 review system options, create your system code in the field below and include your quantity.
 For the canopies/pendants, use the field beside each product name.
 Submit to quotes@zaneen.com to receive a formal BOM and finalized model numbers.



UPON REQUEST
 Additional Options _____
 Fixture Diameter _____
 Canopy Configuration _____

EXAMPLE D10ECLIP-MOD-SYS-UNV-DN

SYSTEM BUILD CODE: D10ECLIP-MOD-SYS- **qty**

ELECTRICAL	Voltage	Dimming
	UNV - 120/277V	DN - Non Dim DP - Phase Dim (Triac/ELV)

CANOPY		BUILD CODE EXAMPLE: D109155-NIC	FINISHES OPTIONS: See page 5 for color options and use 3 digit letters to indicate your choices
MODULES	WITH COMPOSITION DRIVER 30W	D109155-	qty
		Finish ◆ _____ (3 colors)*	
	*Black canopy with cover plate in 3 color options.		
WITH COMPOSITION DRIVER 60W	D109156-	qty	
	Finish ◆ _____ (3 colors)*		
*Black canopy with cover plate in 3 color options.			
WITH COMPOSITION DRIVER 100W	D109157-	qty	
	Finish ◆ _____ (3 colors)*		
*Black canopy with cover plate in 3 color options.			

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

CANOPY

FINISHES OPTIONS:

See page 5 for color options and use 3 digit letters to indicate your choices

MODULES

	D109158-	qty
	Finish (3 colors)* *Black canopy with cover plate in 3 color options.	

	D109159-	qty
	Finish (3 colors)* *Black canopy with cover plate in 3 color options.	

ECLIPSE RINGS

PENDANTS

	D1010010-	qty	
	Dimming DN - Non Dim DP - Phase Dim	CCT: >90 CRI 24K - 2400K 28K - 2800K 30K - 3000K	Finish (3 colors)

	D1010011-	qty	
	Dimming DN - Non Dim DP - Phase Dim	CCT: >90 CRI 24K - 2400K 28K - 2800K 30K - 3000K	Finish (3 colors)

	D1010012-	qty	
	Dimming DN - Non Dim DP - Phase Dim	CCT: >90 CRI 24K - 2400K 28K - 2800K 30K - 3000K	Finish (3 colors)

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

PENDANTS

ECLIPSE RINGS

FINISHES OPTIONS:

See page 5 for color options and use 3 digit letters to indicate your choices

ECLIPSE Ø1180		D1010013-			qty	
Wattage: 45W		Dimming	CCT: >90 CRI	Finish	Delivered Lumen (lm)	
		DN - Non Dim DP - Phase Dim	24K - 2400K 28K - 2800K 30K - 3000K	_____ (3 colors)	2800K	2250
ECLIPSE Ø1400		D1010014-			qty	
Wattage: 52.8W		Dimming	CCT: >90 CRI	Finish	Delivered Lumen (lm)	
		DN - Non Dim DP - Phase Dim	24K - 2400K 28K - 2800K 30K - 3000K	_____ (3 colors)	2800K	2640
ECLIPSE Ø1600		D1010015-			qty	
Wattage: 60W		Dimming	CCT: >90 CRI	Finish	Delivered Lumen (lm)	
		DN - Non Dim DP - Phase Dim	24K - 2400K 28K - 2800K 30K - 3000K	_____ (3 colors)	2800K	3000
ECLIPSE Ø1800		D1010016-			qty	
Wattage: 67.8W		Dimming	CCT: >90 CRI	Finish	Delivered Lumen (lm)	
		DN - Non Dim DP - Phase Dim	24K - 2400K 28K - 2800K 30K - 3000K	_____ (3 colors)	2800K	3390
ECLIPSE Ø2000		D1010017-			qty	
Wattage: 75.6W		Dimming	CCT: >90 CRI	Finish	Delivered Lumen (lm)	
		DN - Non Dim DP - Phase Dim	24K - 2400K 28K - 2800K 30K - 3000K	_____ (3 colors)	2800K	3780

ECLIPSE MODULAR SYSTEM SPECIFICATION SHEET

PROJECT _____
TYPE _____
NOTES _____
QUANTITY _____
DATE _____

FINISH COLORS

Nickel - **NIC**



Brass - **BRA**



Black Brass - **BBR**



Digital: Not all screens are calibrated the same, and therefore, colors will appear differently between screens.

Physical: When texture is involved, there will be variations in color, character and tone within a product series and between product families.

LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)

PROJECT _____
TYPE _____
NOTES _____
QUANTITY _____
DATE _____

Insert custom drawing here or attach with additional pages

