

KIT POP UP SURFACE SYSTEM SPECIFICATION SHEET

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____



DESIGN | KIT POP-UP

KIT POP-UP offers unique solutions with a range of options of colors, designs and sizes. Kit surface system is available for wall mounted with a bracket, and accompanied with fixed or mobile arms to direct the light where desired.



There are 7 different lampshades and numerous cord colors options to chose from. Let your imagination run away and design your own set.

SYSTEM OVERVIEW



KIT POP UP SURFACE SYSTEM SPECIFICATION SHEET

PROJECT _____
 TYPE _____
 NOTES _____
 QUANTITY _____
 DATE _____

SYSTEM GUIDE

To make your product selection and complete system specification, proceed with the following:
 review system options, create your system code in the field below and include your quantity.
 For the canopies/pendants, use the field beside each product name.
 Submit to quotes@zaneen.com to receive a formal BOM and finalized model numbers.



UPON REQUEST
 Additional Options _____
 Special Cord Colors _____
 Cable Length _____

EXAMPLE D11KITPOP-SUR-SYS-120

SYSTEM BUILD CODE: D11KITPOP-SUR-SYS- **qty**

ELECTRICAL	Voltage	Lamp Base
	120 - 120V 277 - 277V (Upon request)	E26

CANOPY		BUILD CODE EXAMPLE: D113034-MBK	FINISHES OPTIONS: See page 4 for color options and use 3 digit letters to indicate your choices
MODULES	WALL FIXED ARM 	D113034-	qty
	Finish ◆ _____ (2 colors)		
	WALL ADJUSTABLE ARM - 500 	D113035-	qty
Finish ◆ _____ (2 colors)			
WALL ADJUSTABLE ARM - 800 	D113036-	qty	
Finish ◆ _____ (2 colors)			








PROJECT _____
 TYPE _____
 NOTES _____
 QUANTITY _____
 DATE _____

PENDANT

LAMPSHADES

FINISHES OPTIONS:

See page 4 for color options and use 3 digit letters to indicate your choices


<p>BANYO Ø300</p> 	<p>D119000- qty</p> <p>Finish</p> <p>◆ _____</p> <p>(14 colors)</p>
<p>DRUM Ø180</p> 	<p>D119001- qty</p> <p>Finish</p> <p>◆ _____</p> <p>(14 colors)</p>
<p>DRUM Ø300</p> 	<p>D119002- qty</p> <p>Finish</p> <p>◆ _____</p> <p>(14 colors)</p>
<p>UKELELE Ø260</p> 	<p>D119003- qty</p> <p>Finish</p> <p>◆ _____</p> <p>(14 colors)</p>
<p>UKELELE Ø350</p> 	<p>D119004- qty</p> <p>Finish</p> <p>◆ _____</p> <p>(14 colors)</p>
<p>KORA Ø240</p> 	<p>D119005- qty</p> <p>Finish</p> <p>◆ _____</p> <p>(14 colors)</p>
<p>KORA Ø350</p> 	<p>D119006- qty</p> <p>Finish</p> <p>◆ _____</p> <p>(14 colors)</p>

KIT POP UP SURFACE SYSTEM SPECIFICATION SHEET


PROJECT _____
TYPE _____
NOTES _____
QUANTITY _____
DATE _____

FINISH COLORS - CANOPY ◆

Matte Black - **MBK**



White - **WHI**



FINISH COLORS - LAMPSHADE CORDS ◆

Beige - **BEI**



Black - **BLK**



Blue - **BLU**



Cognac - **COG**



Dark Green - **DGN**



Gray - **GRY**



Mocha - **MOC**



Maroon - **MRN**



Mustard - **MUS**



Olive - **OLV**



Silver - **SIL**




Stone - **STN**








































































Terracotta - **TER**













White - **WHI**













LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimnable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)

KIT POP UP SURFACE SYSTEM SPECIFICATION SHEET

PROJECT _____
TYPE _____
NOTES _____
QUANTITY _____
DATE _____

Insert custom drawing here or attach with additional pages

