

SYMPHONY MODULAR SYSTEM SPECIFICATION SHEET

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____




DESIGN | SYMPHONY

SYMPHONY is a collection of suspension lighting solutions that can transport you into a recital with its diffusion of light. The glass lampshade features a magnetization system that creates a magnetic field, allowing the sphere to rotate around the ball joint on the axis. A very flexible and functional luminaire, Symphony allows you to rotate the shade to direct the light as necessary to either dilute it or envelop the atmosphere. The minimalistic and unique design of this collection gives it great mobility, easily adapting to the needs of a space at any given moment and therefore creating a connection between the light and the user. The system consists of a pendant lamp with two different shade options with the flexibility to be clustered in groups.



SYSTEM OVERVIEW



PROJECT _____
 TYPE _____
 NOTES _____
 QUANTITY _____
 DATE _____

SYSTEM GUIDE

To make your product selection and complete system specification, proceed with the following:
 review system options, create your system code in the field below and include your quantity.
 For the canopies/pendants, use the field beside each product name.
 Submit to quotes@zaneen.com to receive a formal BOM and finalized model numbers.



UPON REQUEST
 Additional Options _____
 277V

EXAMPLE D9SYMP-MOD-SYS-120

SYSTEM BUILD CODE: D9SYMP-MOD-SYS- **qty**

ELECTRICAL

Voltage	Lamp Base
120 - 120V	G9
277 - 277V (Upon request)	

MODULES

CANOPY		
FOR 2 TO 6 LIGHTS	D99141	qty
	Description	
	Finished in black lacquer for 2, 3, 4, 5, up to 6 suspensions. Includes 6 hooks in polycarbonate injected for fix and suspending cables.	
FOR 7 TO 12 LIGHTS	D99142	qty
	Description	
	Finished in black lacquer for 7, 8, 9, 10, 11, up to 12 suspensions. Includes 12 hooks in polycarbonate injected for fix and suspending cables.	

PENDANT

SYMPHONY		
SYMPHONY Ø90	D91247	qty
Wattage: 9.6W 	Description	
	Glossy opal blown glass with injected polycarbonate support, finished in matte black lacquer. Model suspended by black electric cable. Bulb not included.	

PROJECT _____
 TYPE _____
 NOTES _____
 QUANTITY _____
 DATE _____

LAMPSHADE		BUILD CODE EXAMPLE: D99123-AGL	
ACCESSORIES	Ø300	D99123-	qty
	<p style="text-align: center;">Ø300mm 11 13/16"</p>	Finish ◆ _____ (3 colors - choose 3 letter code below) <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> AGL Anthracite Gray Lacquer </div> <div style="text-align: center;"> MCL Metallic Copper Lacquer </div> <div style="text-align: center;"> MKL Mink Lacquer </div> </div>	
	Ø450	D99126-	qty
	<p style="text-align: center;">Ø450mm 17 13/16"</p>	Finish ◆ _____ (3 colors - choose 3 letter code below) <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> AGL Anthracite Gray Lacquer </div> <div style="text-align: center;"> MCL Metallic Copper Lacquer </div> <div style="text-align: center;"> MKL Mink Lacquer </div> </div>	

LEGEND

	floor-mounted		pivotal		special LED (upon request) RGB, RGBW, tunable, gold+, meat+, art+, fashion+
	wall and ceiling: recessed and surface mounted		rotating		warm dim / natural dimming LED
	ceiling-mounted and wall-mounted		illuminate tilted		rechargeable battery powered
	wall-mounted		color of suspension cable		fixture with natural vivid LED (upon request)
	omni-directional light distribution		length of suspension cable		color rendering index
	direct light distribution		reflector degree selection		color temperature
	direct/indirect light distribution		super spot		lumen (luminous flux)
	indirect light distribution		lens		efficacy (lumens per watt)
	asymmetric light distribution		lens pack		Unified Glare Rating (UGR) range from 5-40
	aura light distribution		shine ring		marine grade (AISI 316 stainless steel)
	round wall or ceiling cut-out		integrated shine ring with diffuser		walk on
	square wall or ceiling cut-out		free individual colors 01-29		drive on
	the supplied jig specifies the cutout dimensions		individual colors: 00 (free of charge), 01-25 (extra charge)		Dark Sky Compliance
	minimum distance (meters) lamp - object		luminaire part to be colored (F1)		Americans with Disabilities Act (less than 4" off the wall located between 27"-84" from floor)
	recessed depth		luminaire part to be colored (F2)		lamp protected against explosion
	ceiling thickness in mm		luminaire part to be colored (F3)		blown glass using traditional methods by master glass blower
	ceiling thickness selection		luminaire part to be colored (F4)		acoustic material
	dimmable DP (phase), DV (0-10V), DD (dali), DS (step-dim)		luminaire part to be colored (F5)		protection class I, protection insulation
	included or excluded LED driver/transformer/control gear		color of 3-circuit adaptor		protection class II, protection insulation
	separately switchable		indirect diffuser		ETL Certified to UL and CSA Standards
	sensor		direct diffuser		UL Certified to UL and CSA Standards
	remote control		ball-proof (upon request)		CSA Certified to UL and CSA Standards
	available upon request		accessory		Certified for North American Standards

IP RATING

	protected against ingress of solid bodies greater than 12.5mm (finger)
	protected against ingress of solid bodies greater than 2.5mm protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) no protection against the ingress of moisture
	protected against ingress of solid bodies greater than 1mm (wire) protected against sprays of water up to 60 degrees from the vertical (rain)
	protected against ingress of solid bodies greater than 1mm (wire) protected against water splashed from all directions
	protected against limited ingress of dust (wet rooms/covered outdoor areas) protected against water splashed from all directions
	protected against ingress of dust protected against jets of water
	protected against ingress of dust protected against powerful jets of water or heavy seas
	protected against ingress of dust protected against immersion of water between 15cm - 1m for 30 minutes
	protected against ingress of dust protected against immersion of water under pressure for long periods

IK RATING

	protected against 0.14 joules impact (equivalent to 0.25kg mass dropped from 56mm above the surface)
	protected against 0.2 joules impact (equivalent to 0.25kg mass dropped from 80mm above the surface)
	protected against 0.35 joules impact (equivalent to 0.25kg mass dropped from 140mm above the surface)
	protected against 0.5 joules impact (equivalent to 0.25kg mass dropped from 200mm above the surface)
	protected against 0.7 joules impact (equivalent to 0.25kg mass dropped from 280mm above the surface)
	protected against 1 joules impact (equivalent to 0.25kg mass dropped from 400mm above the surface)
	protected against 2 joules impact (equivalent to 0.5kg mass dropped from 400mm above the surface)
	protected against 5 joules impact (equivalent to 1.7kg mass dropped from 300mm above the surface)
	protected against 10 joules impact (equivalent to 5.0kg mass dropped from 200mm above the surface)
	protected against 20 joules impact (equivalent to 5.0kg mass dropped from 400mm above the surface)

PROJECT	_____
TYPE	_____
NOTES	_____
QUANTITY	_____
DATE	_____

Insert custom drawing here or attach with additional pages

