

Architectural

Bioniq Evo




ZANEEN





BIONIQ is a professional lighting solution designed for projects where light must be precise, controlled and calm. It delivers clarity without visual noise, allowing architecture to remain in focus. A tool shaped by intention, placing light exactly where it is needed: quietly, reliably and with purpose.

bioniq



designed to be perfect. engineered to be simple.

The trimless version of BIONIQ is designed to integrate seamlessly into the ceiling, becoming part of the architecture. A specially developed PROLICHT double-level hole saw ensures precise ceiling preparation and a perfectly flush result. Simple to install, clean in appearance.



beam control

SPOT to WIDE FLOOD beam distributions with high-performance optics ensure precise and efficient lighting.



optics

Optional accessories such as honeycombs, linear and spread lenses allow accurate beam shaping to suit project requirements.

light colours


From super warm to functional white light, BIONIQ offers a broad range of colour temperatures.

With the introduction of 2400 K, the system is ideal for creating warm, cosy atmospheres - especially in residential and hospitality applications.



ingress protection

Sealed construction with IP65 protection as standard ensures durability in demanding environments. The BIONIQ WALLWASH version is available with IP20, optimised for vertical illumination applications.



zero light leakage


A light-tight rear design prevents unwanted light emission. Light is directed exclusively forward, ensuring clean integration in perforated or acoustic ceilings.

secondary reflector options

Different reflector finishes allow precise visual fine-tuning of the light appearance.

In addition to the optional glossy black ARC (Anti-Reflection Coated) cone for reduced glare without compromising efficiency, chrome, matt white and matt black finishes are available.

All PROLICHT colours can also be specified for further visual integration.



precise adjustment

Smooth rotation up to 350° and tilting up to 30° allow accurate on-site alignment. Visible degree markings ensure consistent results across multiple luminaires.



trimless



BIONIQ

DIMENSION

H 86 - 120: \varnothing 48 - 87 mm

LIGHT OUTPUT


218 - 2790 lm

POWER

8.03 - 21.91 W

LED / CCT

2400 K, 2700 K, 3000 K,
3500 K, 4000 K
TUNABLE WHITE



BIONIQ PINHOLE

DIMENSION

H 95: \varnothing 67 mm

LIGHT OUTPUT

289 - 951 lm

POWER

12.32 - 12.84 W

LED / CCT

2400 K, 2700 K, 3000 K,
3500 K, 4000 K
TUNABLE WHITE



BIONIQ WALLWASH

DIMENSION

H 86 - 95: \varnothing 48 - 67 mm

LIGHT OUTPUT

324 - 1029 lm

POWER

5.5 - 12.31 W

LED / CCT

2400 K, 2700 K, 3000 K,
3500 K, 4000 K
TUNABLE WHITE

recessed



BIONIQ

DIMENSION

H 86 - 125: \varnothing 62 - 108 mm

LIGHT OUTPUT

218 - 2790 lm

POWER

8.03 - 21.91 W

LED / CCT

2400 K, 2700 K, 3000 K,
3500 K, 4000 K



BIONIQ PINHOLE

DIMENSION

H 95: \varnothing 82 mm

LIGHT OUTPUT

289 - 951 lm

POWER

12.32 - 12.84 W

LED / CCT

2400 K, 2700 K, 3000 K,
3500 K, 4000 K
TUNABLE WHITE



BIONIQ WALLWASH

DIMENSION

H 86 - 95: \varnothing 62 - 82 mm

LIGHT OUTPUT

324 - 1029 lm

POWER

5.5 - 12.31 W

LED / CCT

2400 K, 2700 K, 3000 K,
3500 K, 4000 K
TUNABLE WHITE



ZANEEN

Internationally recognized North American provider of premium European lighting, offering innovative solutions across four divisions.

Projects

Inspiration

For more information, please contact Zaneen or your local representative.

zteam@zaneen.com

T 1-800-388-3382

zaneen.com

ARCHITECTURAL

Innovative solutions for precision lighting.

Products

DESIGN

Extensive range of material, form and style.

Products

EXTERIOR

Cutting-edge technology meets craftsmanship.

Products

CUSTOM

Crafting bespoke luminaires with expertise.

About